

CONTROL BOARD 12055902

INSTALL INSTRUCTIONS

Replaces MPNs: 12055902, 12025902, 12025912, 12155900, 12155900R, 12155912, H7881

Before Installing

- **ALWAYS** unplug the unit before beginning any work
 - Allow the unit to cool completely if recently used
 - Work in a well-lit area with proper tools
 - Ensure there are no pellets in the hopper assembly
-

Installation Steps

1. Unplug the stove from the power source
2. Remove the fastening screws from the old control board.
3. Pull the control board out from the control board slot in the stove.
4. Disconnect the connectors to the Main Wiring Harness (6 Position connector), and the thermostat terminal if you use a TSTAT connection (connector at the bottom of the control board with yellow wires) to remove the old control board.
5. Reconnect connectors to the new control board in the same locations as the old control board. (if you are not using a TSTAT on the stove, connect the two spade connectors at the bottom of the new board together with a jumper wire or connect your wiring harness yellow wires and connect those together at the TSTAT bridge).
6. Push the new board into the control board slot in the stove and replace the fastening screws.

DIAGRAMS:

- Verify all connections are secure
- Ensure all wiring is not in proximity of moving parts
- Test motor operation before closing panels
- Check for any unusual noises or vibrations

If you encounter any issues during installation, consult your owner's manual or contact technical support via our [contact form](#).