

BAFFLE BOARDS & BLANKET 2208C

INSTALLATION INSTRUCTIONS

Replaces MPNs: 250-03598, 250-03599

Before Installing

- **ALWAYS** unplug the unit before beginning any work
 - Allow the unit to cool completely if recently used
 - Work in a well-lit area with proper tools
-

Installation Steps

1. Disconnect Power

- Ensure the unit is completely cooled down and drained of power.
- Unplug the stove from the powersource.

2. Access the Unit

- Open the main door to the unit. The baffle will be sitting on the inside of the stove firebox, typically laying on top of the air tubes in the top of the unit.
- The two front air tubes will need to be removed to access the baffle. Before removal, make sure to label each of the tubes with numbers starting with the tube in front then progressing toward the back
- Each of these tubes can be removed by lifting the front baffle up and twisting the tube forward.
- Remove the bypass assembly above the baffle boards and blanket.
 - The bypass yoke assembly can be removed by pulling the bypass forward and unscrewing the extension rod from the yoke. The yoke may then be removed through the bypass hole.
 - The bypass slider may also be removed through the bypass hole.

- Remove the bypass support by lifting it up from underneath in the firebox, and then turn it sideways to slide it forward and remove it from the front.

3. Remove Old Baffle Board & Blanket

- Carefully remove the baffle blanket. This part may be fragile and covered in flashing.
- Remove the baffle boards to finalize the removal.

4. Install New Baffle Board & Blanket

- Insert the new baffle boards to the mounting location. Ensure the boards are oriented in the same positions as the old boards removed prior.
- Carefully insert the baffle blanket so it lays on top of the baffle boards.

5. Connect Power

- Reinstall the bypass assembly starting with the support, the slider, and then the yoke. Ensure each part is oriented in the same position as before
- Install the air tubes to the manifold in the reverse order they were removed in.
- Close the main door to the unit.
- Plug the stove's power cord into the power source.
- Your new baffles and blanket are installed and ready to use.

Post-Installation Check

- Verify all connections are secure
- Test the seal of the door to ensure proper fitment. The door should be sealed tightly when both the handle is secured and the gasket is at proper thickness.

- Check the baffle boards, blankets, and air tubes for damage before final installation.

Support

If you encounter any issues during installation, consult your owner's manual or contact technical support via our contact form.