

# BAFFLE BOARD 2431A

## INSTALLATION INSTRUCTIONS

Replaces MPNs: 3120-390

---

### Before Installing

- **ALWAYS** unplug the unit before beginning any work
  - Allow the unit to cool completely if recently used
  - Work in a well-lit area with proper tools
- 

### Installation Steps

#### 1. Disconnect Power

- Ensure the unit is completely cooled down and drained of power.
- Unplug the stove from the powersource.

#### 2. Access the Unit

- Locate the two nuts on the left and right sides of the stove's top casting.
- Remove the nuts with a 10mm wrench or socket and then lift the top straight up and off the stove body.
- The baffle and the front baffle support can be accessed from the top of the firebox once the top has been removed..

#### 3. Remove Old Baffle

- Remove the countersunk screws that retain the front baffle support using the Phillips screwdriver and move the baffle support away from the baffle board.
- Remove the old ceramic baffle and any remaining old cement.

#### 4. Install New Baffle

- Place the new baffle in the top of the firebox
- Secure the new baffle by returning the baffle support to its original position and replacing the screws. It is not necessary to replace the cement seam around the outer edge of the baffle since the screws can be snugged to bypass the need for cement.

## 5. Connect Power

- Reinstall the top casting back onto the stove body. Secure the casting to the stove with the two nuts removed in Step 1.
  - Plug the stove's power cord into the power source.
  - Your new baffle is installed and ready to use.
- 

## Post-Installation Check

- Verify all connections are secure
  - Check the baffle and bracket for damage before final installation.
- 

## Support

If you encounter any issues during installation, consult your owner's manual or contact technical support via our contact form.