

BAFFLE BOARD 2435A

INSTALLATION INSTRUCTIONS

Replaces MPNs: 3120-470

Before Installing

- **ALWAYS** unplug the unit before beginning any work
 - Allow the unit to cool completely if recently used
 - Work in a well-lit area with proper tools
-

Installation Steps

1. Disconnect Power

- Ensure the unit is completely cooled down and drained of power.
- Unplug the stove from the powersource.

2. Access the Unit

Open the main door to the unit. The baffle(s) will be sitting on the inside of the stove firebox, typically laying on top of the reburn tubes in the top of the unit.

3. Remove Old Baffle

- Lift the front of the baffle to unlock the shelf tabs from the baffle.
- Pull the baffle forward and let it drop down to remove the baffle through the front door.

4. Install New Baffle

- Insert the baffle and position it so it lays on top of the reburn tubes.
- Push the new baffle into the unit until the baffle is locked in by the shelf tabs.

5. Connect Power

- Close the main door of the stove. Ensure the door is sealed when closed.
 - Plug the stove's power cord into the power source.
 - Your new baffle is installed and ready to use.
-

Post-Installation Check

- Verify all connections are secure
 - Test the seal of the door to ensure proper fitment. The door should be sealed tightly when both the handle is secured and the gasket is at proper thickness.
 - Check the baffles and blankets for damage before final installation.
-

Support

If you encounter any issues during installation, consult your owner's manual or contact technical support via our contact form.