

DOOR HANDLE 25692-AMP INSTALLATION INSTRUCTIONS

Replaces MPNs: 25692

Before Installing

- **ALWAYS** unplug the unit before beginning any work
 - Allow the unit to cool completely if recently used
 - Work in a well-lit area with proper tools
-

Installation Steps

1. Disconnect Power

- Ensure the unit is completely cooled down and drained of power.
- Unplug the stove from the powersource.

2. Access the Unit

- Open the main door to the unit. The handle will be fastened to the door.
- Remove the spring handle grip from the end of the handle

3. Remove Old Door Handle

The handle is held in place to the door with a roll pin. With a nut driver and hammer, tap the rolling pin out from the handle and set the pin aside in a safe place. This will free the handle from the door frame.

4. Install New Door Handle

- Position the new handle onto the door frame. The hooked part of the handle should be on the inside of the door and oriented in the same direction as the old door handle.

- Secure the handle to the door frame using the roll pin removed in Step 3. The pin must be gently tapped into place and sit snug through the door handle. If the roll pin is damaged or doesn't fit tightly, the pin will need to be replaced.

5. Connect Power

- Install the spring handle grip to the stem of the handle.
- Close the door to the stove. Ensure the door is sealed when closed
- Plug the stove's power cord into the power source.
- Your new door handle is installed and ready to use.

Post-Installation Check

- Verify all connections are secure
- Test the seal of the door to ensure proper fitment. The door should be sealed tightly when both the handle is secured and the gasket is at proper thickness.
- Check for any openings in the door seal. Closing the door on a piece of paper then attempting to pull it out would be the best method; The paper should not be able to move if that place on the gasket is completely sealed. If the paper is easy to pull out,

Support

If you encounter any issues during installation, consult your owner's manual or contact technical support via our contact form.