

BAFFLE & BLANKET KIT 2803C

INSTALLATION INSTRUCTIONS

Replaces MPNs: 88158, 88159, 88160

Before Installing

- **ALWAYS** unplug the unit before beginning any work
 - Allow the unit to cool completely if recently used
 - Work in a well-lit area with proper tools
-

Installation Steps

1. Disconnect Power

- Ensure the unit is completely cooled down and drained of power.
- Unplug the stove from the powersource.

2. Access the Unit

- Open the main door to the unit. The baffles and blanket will be sitting on the inside of the stove firebox, typically laying on top of the reburn tubes in the top of the unit. The blanket will be stacked on top of the baffle boards.
- On most units, 1 to 2 of the reburn tubes may need to be removed to access the baffles and blanket. These tubes can be removed by removing the retaining clip and bolt holding the tube in place.
 - It is recommended to apply penetrating oil (like PB blaster or WD40) to the bolt to ease removal. Allow the bolt time to soak in the oil if applied.
- Removal of the reburn tubes may not be necessary for removal on some units. Refer to your owner's manual for further details.

3. Remove Old Baffle & Blanket

Carefully pull both baffles and the baffle blanket off the reburn tubes and out of the unit.

Note: It is recommended to replace the blanket when replacing the baffle, especially if the blanket looks frayed and damaged.

4. Install New Baffle & Blanket

- Lay the new blanket onto the new baffles.
- Insert the new baffles and blanket onto the reburn tubes.

5. Connect Power

- Reinstall the reburn tubes removed in Step 2. Secure the tubes to the unit with the removed retaining clips and bolts.
- Close the main door of the stove. Ensure the door is sealed when closed.
- Plug the stove's power cord into the power source.
- Your new baffles and blanket is installed and ready to use.

Post-Installation Check

- Verify all connections are secure
- Test the seal of the door to ensure proper fitment. The door should be sealed tightly when both the handle is secured and the gasket is at proper thickness.
- Check the baffles and blankets for damage before final installation.

Support

If you encounter any issues during installation, consult your owner's manual or contact technical support via our contact form.

