

THERMOMETER PROBE 7000TH3 INSTALLATION INSTRUCTIONS

Replaces MPNs: 7000TH3, 948, 0000TH3

Before Installing

- **ALWAYS** unplug the unit before beginning any work
 - Allow the unit to cool completely if recently used
 - Work in a well-lit area with proper tools
-

Installation Steps

1. Disconnect Power

- Ensure the unit is completely cooled down and drained of power.
- Unplug the grill from the powersource.

1. Access the unit

- Locate the thermometer probe on your unit. This is typically attached to the rear surface of the unit in proximity to the rear of the combustor. If your unit does not have one installed, locate a predrilled hole with a cap or cover in the location mentioned and proceed to Step 3.
- If your unit did not originally feature a predrilled hole, your unit may require a hole to be drilled in the area mentioned prior. It is also advised to consult with your stove's original dealer for the location of the proper placement of the hole. Proceed to Step 3 in this case

2. Remove Old Thermometer

The thermometer does not require fasteners to be installed or removed. pull the thermometer out from the slot on the unit to remove it.

3. Install New Thermometer

- If your unit features neither a thermometer probe nor a predrilled hole for said probe, it may be necessary to drill your own 1/4" hole and then insert the thermometer. This would normally be done in an area which would place the probe just behind the catalytic combustor (toward the chimney).
 - The hole must be drilled into the unit at least 1/4" away from the combustor, **be careful** not to drill into the combustor.
- Insert the stainless steel eyelet provided with your thermometer into the hole.
- Insert the thermometer into the eyelet with the probe inserted first. The thermometer should just sit in the eyelet on the unit.

4. Connect Power

- Connect the stove's power cord to the power source.
- Your new thermometer is ready to use.

Post-Installation Check

- Verify all connections are secure
- Test thermometer operation before final assembly
- Check for any unusual temperature spikes on the gauge

Support

If you encounter any issues during installation, consult your owner's manual or contact technical support via our contact form.

