

DOOR LATCH KIT 93-73508

INSTALLATION INSTRUCTIONS

Replaces MPNs: 93-73508

Before Installing

- **ALWAYS** unplug the unit before beginning any work
 - Allow the unit to cool completely if recently used
 - Work in a well-lit area with proper tools
-

Installation Steps

1. Disconnect Power

- Ensure the unit is completely cooled down and drained of power.
- Unplug the stove from the powersource.

2. Access the Unit

Open the side door to the unit. The latch will be fastened to the frame of the door.

3. Remove Old Door Latch

- Prior to disassembly, take clear photos of the orientation of the latch for reference. The new latch will need to be oriented in the same position as this old latch once installed and use the same number of brass spacer washers.
- Remove the two setscrews located in the latch assembly 5-32" allen wrench. When loose, pull apart and remove the outer and inner portions of the latch from the stove.
- On some older units made before 2005, the catch and catch spacer will also need to be removed from the stove. This can be done by removing the two phillips head screws holding it in place.

- Remove the bolt and wooden handle from the crank with a flat tip screwdriver. Save these to be installed on the new latch assembly.

4. Install New Door Latch

- If the catch was removed in Step 3, Install the new catch and spacer with the two screw removed from the old catch
- Install one brass spacer to the latch shaft.
- Push the threaded end of the latch shaft through the door so the threads are on the outside of the door.
- Position the washer, and then the coil spring onto the threaded end of the latch shaft on the outer side of the door assembly.
- Turn and adjust the crank until there is approximately 1/8" space between the crank and the washer.
- Align the setscrew hole in the crank with the flat part on the latch shaft. Insert and tighten a setscrew into the hole of the crank with the 5/32 hex wrench to secure it into place.
- The assembly should be assembled as depicted in the diagram on page 4 if correctly installed.
- Install the bolt and wooden handle removed in step 3. .

5. Connect Power

- Close the door to the stove. Ensure the door is sealed when closed
- Plug the stove's power cord into the power source.
- Your new door handle is installed and ready to use.

Post-Installation Check

- Verify all connections are secure
- Test the seal of the door to ensure proper fitment. The door should be sealed tightly when both the handle is secured and the gasket is at proper thickness.
- Check door seals using the "dollar bill test" before final assembly. Shut the door on a dollar bill in various locations. If the bill pulls out without any

resistance, then your stove's door isn't sealed properly. Add or remove spacers from the inside of the latch to adjust gasket pressure. Remove a spacer to draw the door tighter. If additional washers are needed, the original washers can be reused.

Support

If you encounter any issues during installation, consult your owner's manual or contact technical support via our contact form.

Diagram

