

GREASE TRAP LINER BAC404 INSTALLATION INSTRUCTIONS

Replaces MPNs: BAC404

Before Installing

- **ALWAYS** unplug the unit before beginning any work
 - Allow the unit to cool completely if recently used
 - Work in a well-lit area with proper tools
-

Installation Steps

1. Disconnect Power

- Ensure the unit is completely cooled down and drained of power.
- Unplug the grill from the power source.

2. Access the Unit

Locate the grease trap in the grill. The grease trap is typically accessible from the side of the grill and pulls out as a drawer.

3. Remove Old Drip Tray Liner

- Pull out the grease trap until it stops in place.
- Lift the old grease liner out from the trap and dispose of the old liner.

5. Install New Drip Tray Liner

- Insert the new grease trap liner into the grease trap.
- Push the grease trap back into the compartment.

6.. Connect Power

- Plug the grill's power cord into the power source.

- Your new drip tray is installed and ready to use.
-

Post-Installation Check

- Verify the drip sits flush inside the grill before final assembly
 - Ensure the drip tray drains into the drip bucket sufficiently.
 - Be careful not to touch the grill while testing or operating, allow the unit to cool completely before making any adjustments.
-

Support

If you encounter any issues during installation, consult your owner's manual or contact technical support via our contact form.