

FAN209

Induction Fan

INSTALLATION INSTRUCTIONS

Before Installing

- **ALWAYS** unplug the unit before beginning any work
 - Allow the unit to cool completely if recently used
 - Work in a well-lit area with proper tools
-

Installation Steps

1. Power Disconnection

Unplug the unit from the power source.

2. Access the unit.

- remove the access panel on the hopper to access the fan.
- Tip: This fan can be found in the mechanical area inside the hopper burner assembly, under the hopper. It faces upward, is usually white, and has orange wires leading to it.

3. Disconnect Wiring

Unplug only the orange wire Molex connector from the control board.

4. Remove Old Fan

- Remove the 4 mounting screws that hold the Traeger draft induction fan using a 1/4" wrench or nut driver.
- Pull the fan out of the motor area from underneath the hopper.

5. Install New Fan

Install the replacement induction fan using the original 4 mounting screws.

Note: This fan motor is **NOT** used on any grill that has the hopper mounted on the right-side of the unit or any grill that uses a D2 controller. All of the portable grills, Scout, Ranger, PTG+ use part FAN209-R instead, which has only 3 support arms.

6. Connect Wiring

Plug the orange wire Molex connector back to the control board.

7. Final Assembly

Reinstall access panel securely.

10. Power Connection

Plug the stove back into the power source.

Post-Installation Check

- Verify all connections are secure
 - Test blower operation before closing panels
 - Check for any unusual noises or vibrations
-

Support

If you encounter any issues during installation, consult your owner's manual or contact technical support via our contact form.