

PROOF OF FIRE SWITCH H5887

INSTALL INSTRUCTIONS

Replaces MPNs: H5887, 12057601, 12150080

Before Installing

- **ALWAYS** unplug the unit before beginning any work
 - Allow the unit to cool completely if recently used
 - Work in a well-lit area with proper tools
 - Ensure there are no pellets in the hopper assembly
-

Installation Steps

1. Unplug the stove
 2. Open the rear access panel. Removal of the access panel may be necessary.
 3. Locate the Proof of Fire switch on the side of the stove where the combustion blower is mounted. The switch is located on the exhaust blower housing.
 4. Loosen the two contact points for the wires on the switch and remove the two fork connectors using a flat head screwdriver.
 5. Remove the two hex screws that hold the switch to the housing using a 1/4" socket wrench.
 6. Install the new switch to the housing. If your new switch does not have screws for connecting the wires, use the screws from the old switch.
 7. Reconnect your wires to the new switch. It does not matter which wire goes on which terminal.
 8. Close the rear access panel. (reattach panel with screws if removed)
-

Post-Installation Check

- Verify all connections are secure
- Ensure all wiring is not in proximity of moving parts

- Test motor operation before closing panels
 - Check for any unusual noises or vibrations
-

Support

If you encounter any issues during installation, consult your owner's manual or contact technical support via our [contact form](#).