

WARMING RACK HDW437

INSTALLATION INSTRUCTIONS

Replaces MPNs: KIT0445

Before Installing

- **ALWAYS** unplug the unit before beginning any work
 - Allow the unit to cool completely if recently used
 - Work in a well-lit area with proper tools
-

Installation Steps

1. Disconnect Power

- Ensure the unit is completely cooled down and drained of power.
- Unplug the grill from the power source.

2. Access the Unit

- Open the main grill lid.
- Locate the warming rack in the grill. The upper grate is mounted in the middle of the grill's cooking space, sitting right above the main cooking grates on the bottom.

3. Remove Old Rack

- Lift the grate out from the mounting holes in the rack side supports and disengage it from the grate grill.
- Pull the old rack out from the grill to remove it.

5. Install New Grate

- Insert the new warming rack into the grill centered side to side with the rear bent edge inserted first. Ensure the 4 mounting "legs" are pointed downward.

- Align the legs with the holes in the rack side supports. Proceed then to insert the legs into the holes until the sides of the grate sits flush to the side supports.

6. Connect Power

- Close the main grill lid.
- Plug the grill's power cord into the power source.
- Your new warming rack is installed and ready to use.

Post-Installation Check

- Verify if the grates sits flush inside the grill before final assembly
- Be careful not to touch the grill while testing or operating, allow the unit to cool completely before making any adjustments.

Support

If you encounter any issues during installation, consult your owner's manual or contact technical support via our contact form.