

GRILL CASTER LEG KIT0140

INSTALLATION INSTRUCTIONS

Replaces MPNs: KIT0140, SUB948

Before Installing

- **ALWAYS** unplug the unit before beginning any work
 - Allow the unit to cool completely if recently used
 - Work in a well-lit area with proper tools
-

Installation Steps

1. Disconnect Power

- Ensure the unit is completely cooled down and drained of power.
- Unplug the grill from the power source.
- Ensure the unit is completely emptied of pellets.

2. Access the Unit

- Before proceeding, verify the leg replacement. This leg typically serves as the front right leg if looking from the front lid of the grill. This may also serve as the rear left leg in some models.
- Remove any loose parts from the grill such as grill grates or drip pans
- Carefully lay the grill on its rear panel to gain easier access to the legs. It is recommended to lay the unit on a mat to prevent damage to the grill body.
 - Ensure to remove obstructive parts such as grill grates and possibly the chimney to prevent internal or external damage to the grill.

3. Remove Old Leg

- Remove the screw on the inside of the leg brace securing the middle portion of the leg.
- Loosen and remove the nut, bolt, and washers from the leg where the leg meets the body of the grill. Reassemble the hardware assembly in the order it was found in and set this to the side.
 - The order should be the bolt, 2 flat washers, the lock washer, and finally the nut. See the diagram on page 4 for reference.
- Pull out the leg from the socket in the grill body to complete removal.

5. Install New Leg

- Insert the new caster leg into the leg socket on the grill. Make sure to align the holes from the leg to the holes in the grill frame.
- Disassemble the hardware assembly from step 3, but leave 1 flat washer on the bolt. Insert the bolt with the flat washer into the leg slot. The head of the bolt should be situated toward the outside of the grill.
- Secure the bolt by first inserting the flat washer, the lock washer, and finally the nut to the threaded part of the bolt. Make sure to just thread the nut but do not fully tighten yet.
- Insert the screw into the hole on the inside of the brace to connect the leg, make sure not to tighten fully yet.
- Reposition the grill so it now stands on the wheels and stands upright.
- Tighten the partially threaded nut and screw to finally secure the leg.

6. Connect Power

- Reinstall any removed parts from step 2 to the grill.
- Plug the grill's power cord into the power source.
- Your new leg is installed and ready to use.



Post-Installation Check

- Verify if the wheels turn and operate normally before final assembly.

- Ensure all connections are secure.
 - Make sure the legs are level to each other. The unit should not be standing slightly tilted or have any short legs if installed correctly.
-

Support

If you encounter any issues during installation, consult your owner's manual or contact technical support via our contact form.

Diagram

