

LID HANDLE KIT0141

INSTALLATION INSTRUCTIONS

Replaces MPNs: KIT0141, HDW329, HDW477

Before Installing

- **ALWAYS** unplug the unit before beginning any work
 - Allow the unit to cool completely if recently used
 - Work in a well-lit area with proper tools
-

Installation Steps

1. Disconnect Power

- Ensure the unit is completely cooled down and drained of power.
- Unplug the grill from the powersource.

2. Access the Unit

Open the main lid to the unit. The handle will be fastened to the front of the lid.

3. Remove Old Lid Handle

The handle is held in place to the door with bolts and washers. With a screwdriver remove each of the handle set screws and washers from the lid one after another. If your unit's handle features mounting bezels in the front of the lid where the handle mounts, carefully remove these when removing the bolts and washers and set these and the bolts and washers aside for later.

4. Install New Door Handle

- Position one end of the new handle onto the lid's mounting holes frame. If bezels were removed in Step 3, position one of the bezels

between the handle end and the lid. Secure the handle end with one each of the bolts and washers from Step 3, but allow enough space on the bolt to position the other end of the handle to the lid.

- Position and securing the other handle end with the remaining bezel, bolt and washer.
- Tightening the bolts to finish securing the handle to the lid. Be careful not to overtighten the bolts, overtightening could risk damaging or breaking off the bolt threads in the handle.

5. Connect Power

- Close the lid to the grill.
 - Plug the grill's power cord into the power source.
 - Your new lid handle is installed and ready to use.
-

Post-Installation Check

- Verify all connections are secure
 - Ensure the handle does not wobble in place on the lid after installation.
-

Support

If you encounter any issues during installation, consult your owner's manual or contact technical support via our contact form.