

DOOR GASKET KIT0252

INSTALLATION INSTRUCTIONS

Replaces MPNs: KIT0252

Before Installing

- **ALWAYS** unplug the unit before beginning any work
 - Allow the unit to cool completely if recently used
 - Work in a well-lit area with proper tools
-

Installation Steps

1. Disconnect Power

- Ensure the unit is completely cooled down and drained of power.
- Unplug the grill from the power source.

2. Access the Unit

Open the grill's main cooking lid. The gasket will be lining the lid.

3. Remove Old Gasket

Carefully pull the old gasket out from the lining of the lid with a flathead screwdriver. Excessive force can risk the clips snapping off the old gasket while connected to the lid, which can prevent proper fitment of the new gasket.

4. Install New Gasket

- Insert and push the new door gasket's retention clips into the holes of the lid liner.
- Ensure the retention clips are entirely pushed in all the way into the holes around the door for secure placement and a firm door seal.

5. Connect Power

- Plug the grill's power cord into the power source.
 - Your new gasket is installed and ready to use.
-

Post-Installation Check

- Verify all connections are secure
 - Ensure the gasket is mounted uniformly.
 - Be careful not to touch the grill while testing or operating, allow the unit to cool completely before making any adjustments.
-

Support

If you encounter any issues during installation, consult your owner's manual or contact technical support via our contact form.