

LIGHT LID SENSOR KIT0633

INSTALL INSTRUCTIONS

Replaces MPNs: KIT0633

Before Installing

- **ALWAYS** unplug the unit before beginning any work
 - Allow the unit to cool completely if recently used
 - Work in a well-lit area with proper tools
 - Ensure there are no pellets in the hopper assembly
-

Installation Steps

1. Turn off and unplug your grill.
 2. Remove smart combustion cover
 3. Locate lid and light sensor cables and disconnect from kirby
 4. Cut zip tie holding light / lid sensor cables
 5. Open hopper lid
 6. Remove screw holding ETL grate and remove ETL grate
 7. Remove remaining screws on the display access panel
 8. Remove display access panel with light / lid sensor attached
 9. Remove screws holding light / lid sensor to access panel
 10. Attach the new lid / light sensor to the access panel and repeat previous steps in the reverse order, adding a new zip tie in place of the one that was cut.
 11. Turn on your grill to see if the issue has been resolved.
-

Post-Installation Check

- Verify all connections are secure
 - Ensure all wiring is not in proximity of moving parts
 - Test motor operation before closing panels
 - Check for any unusual noises or vibrations
-

Support

If you encounter any issues during installation, consult your owner's manual or contact technical support via our [contact form](#).