

POWER BUTTON KIT0687

INSTALL INSTRUCTIONS

Replaces MPNs: KIT0687

Before Installing

- **ALWAYS** unplug the unit before beginning any work
 - Allow the unit to cool completely if recently used
 - Work in a well-lit area with proper tools
 - Ensure there are no pellets in the hopper assembly
-

Installation Steps

1. Turn off and unplug your grill.
2. Remove the hopper service panel.
3. Remove the 6 service panel screws found on the top and bottom of the panel and just under the side P.A.L rail.
4. Pull the panel away from the grill.
5. Inside the hopper, locate the power button near the front.
6. Disconnect the wires from the power button by gripping onto the blue connector and pulling away from the button.
7. Unscrew the nut that holds the button in place.
8. Pull the power button out of the hopper from the front of the grill.
9. Insert the new power button into the hopper.
10. Screw on and hand-tighten the nut to secure the button in place.
11. Plug the blue wiring connector into the power button.
12. Align the hopper panel with the screw holes and tighten the 6 screws you previously removed.

Post-Installation Check

- Verify all connections are secure
- Ensure all wiring is not in proximity of moving parts
- Test motor operation before closing panels
- Check for any unusual noises or vibrations

Support

If you encounter any issues during installation, consult your owner's manual or contact technical support via our [contact form](#).