

POWER STRIP ASSEMBLY KIT0690

INSTALL INSTRUCTIONS

Replaces MPNs: KIT0690

Before Installing

- **ALWAYS** unplug the unit before beginning any work
 - Allow the unit to cool completely if recently used
 - Work in a well-lit area with proper tools
 - Ensure there are no pellets in the hopper assembly
-

Installation Steps

1. Turn off and unplug the grill.
 2. Use an impact driver to remove the screws behind the P.A.L rail on your hopper service panel.
 3. Remove the 6 screws on the top and bottom of the panel and under the P.A.L rail to remove the hopper service panel.
 4. Remove the two screws securing the power strip to the hopper assembly with a Phillips screwdriver.
 5. Disconnect the six connectors.
 6. Connect the six connectors to the new power strip. Ensure the connections are in the same positions as on the previous power strip.
 7. Screw in the two screws to attach the power strip to the hopper assembly.
 8. Reattach the hopper service panel with screws.
 9. Plug in and turn on the grill to ensure the power strip is working properly.
-

Post-Installation Check

- Verify all connections are secure

- Ensure all wiring is not in proximity of moving parts
 - Test motor operation before closing panels
 - Check for any unusual noises or vibrations
-

Support

If you encounter any issues during installation, consult your owner's manual or contact technical support via our [contact form](#).