

SLIDE GRILL ROD PPG20-8 INSTALLATION INSTRUCTIONS

Replaces MPNs: PPG20-8

Before Installing

- **ALWAYS** unplug the unit before beginning any work
 - Allow the unit to cool completely if recently used
 - Work in a well-lit area with proper tools
-

Installation Steps

1. Disconnect Power

- Ensure the unit is completely cooled down and drained of power.
- Unplug the grill from the power source.

2. Access the Unit

- Open the main grill lid.
- Locate the drip tray in the grill. The drip tray is typically mounted inside the burn area under the grill grates. The slide grill rod will be connected to the deflector underneath this tray.
- Remove the grill grates from the grill's cooking area.
- Lift the drip tray out from the grill barrel. The drip tray would typically sit on mounting brackets.

3. Remove Old Slide Rod

- Carefully remove the nut from the end of the slide rod to disengage the rod from the deflector. Ensure not to drop the nut into the grill barrel.
- Pull the old slide rod out through the hole on the side of the grill.

4. Install New Slide Rod

- On the new slide rod, remove the nut closer to the end of the rod.
- Insert the new slide rod into the grill barrel through the hole on the side of the grill.
- Guide the rod through the connecting hole in the grill deflector.
- Secure the rod to the deflector to the end of the rod with the nut removed prior.

5. Connect Power

- Install the drip pan and cooking grates removed in Step 2 to the grill.
- Close the main grill lid.
- Plug the grill's power cord into the power source.
- Your new drip tray is installed and ready to use.

Post-Installation Check

- Verify if all connections are secure.
- Ensure the deflector and slide rod moves smoothly in the grill when operated before final assembly.

Support

If you encounter any issues during installation, consult your owner's manual or contact technical support via our contact form.