

# DOOR LATCH CATCH S.0693 INSTALLATION INSTRUCTIONS

Replaces MPNs: S.0693

---

## Before Installing

- **ALWAYS** unplug the unit before beginning any work
  - Allow the unit to cool completely if recently used
  - Work in a well-lit area with proper tools
- 

## Installation Steps

### 1. Disconnect Power

- Ensure the unit is completely cooled down and drained of power.
- Unplug the stove from the powersource.

### 2. Access the Unit

- Open the main door to the unit.
- Locate the latch catch on the side of the firebox frame along the edge of the opening. The latch catch is typically mounted where it would come in contact with the door handle hook

### 3. Remove Old Latch & Hook

- Loosen and remove the nut on the back of the old latch in the firebox
- Pull out the latch to remove it from the stove.
  - Keep the old latch to the side for adjustment of the new latch for later.

### 4. Install New Latch & Hook

- Install one nut to the new latch catch, you can adjust the placement of this nut based on the position of the nut on the original latch catch as reference.
- Insert the new latch catch into the firebox frame. Ensure the latch is inserted threads first into the front of the frame with the catch section pointing upward.
- Secure the latch to the door frame using the other nut included with the kit to secure the latch. Tighten the nut until it touches the frame, do not tighten completely yet. The latch may need to be adjusted later on
- Close the door to the stove and ensure the door is uniformly sealed and seated even when closed. You can adjust the lats as needed by turning both nuts on the latch catch. Proceed to tighten the nuts until both nuts sit snug to finally secure the latch catch.
  - Always ensure the catch is pointing upward while adjusting the latch catch.

## 5. Connect Power

- Plug the stove's power cord into the power source.
- Your new door latch catch is installed and ready to use.

---

## Post-Installation Check

- Verify all connections are secure
  - Test the seal of the door to ensure proper fitment. The door should be sealed tightly and sit uniformly to the stove when both the handle is secured and the gasket is at proper thickness.
  - Check for any openings in the door seal. Closing the door on a piece of paper then attempting to pull it out would be the best method; The paper should not be able to move if that place on the gasket is completely sealed. If the paper is easy to pull out,
-

## **Support**

If you encounter any issues during installation, consult your owner's manual or contact technical support via our contact form.