

BYPASS HANDLE S.Z2452.B

INSTALLATION INSTRUCTIONS

Replaces MPNs: S.Z2452.B

Before Installing

- **ALWAYS** unplug the unit before beginning any work
 - Allow the unit to cool completely if recently used
 - Work in a well-lit area with proper tools
-

Installation Steps

1. Disconnect Power

- Ensure the unit is completely cooled down and drained of power.
- Unplug the stove from the powersource.

2. Access the Unit

Locate the bypass handle on the unit. The bypass handle typically is connected through a hole on the side of the unit.

3. Remove Old Bypass Handle

- Before removal, take note of the orientation of the handle.
- The bypass handle may be connected to the unit with either a set screw or by being threaded to the bypass rod depending on the model. Remove the set screw or turn the handle counterclockwise to remove the handle from the bypass rod.

4. Install New Bypass Handle

- Position and insert the Bypass rod into the new handle.
- Secure the handle to the rod. Ensure the handle is oriented in the same position as the old handle.

- For models that use a set screw, tighten the set screw to secure the handle.
- For models that thread the handle to the rod, turn the handle clockwise until the handle locks in place.

5. Connect Power

- Plug the stove's power cord into the power source.
 - Your new door handle is installed and ready to use.
-

Post-Installation Check

- Verify all connections are secure
 - Test bypass operation and ensure the handle is secure.
-

Support

If you encounter any issues during installation, consult your owner's manual or contact technical support via our contact form.