

DOOR HANDLE S.Z4044

INSTALLATION INSTRUCTIONS

Replaces MPNs: S.Z4044

Before Installing

- **ALWAYS** unplug the unit before beginning any work
 - Allow the unit to cool completely if recently used
 - Work in a well-lit area with proper tools
-

Installation Steps

1. Disconnect Power

- Ensure the unit is completely cooled down and drained of power.
- Unplug the stove from the powersource.

2. Access the Unit

Open the main door to the unit. The handle will be fastened to the door.

3. Remove Old Door Handle

The handle is held in place to the door frame with two bolts. Simply remove the two bolts fastening the old handle block to the frame free the handle from the door frame.

4. Install New Door Handle

- Position the new handle onto the door frame.
- Secure the handle to the door frame using the two bolts removed in Step 3. Tighten the bolts until snug, do not overtighten. Overtightening the bolts can risk damaging them.

5. Connect Power

- Close the door to the stove. Ensure the door is sealed when closed
 - Plug the stove's power cord into the power source.
 - Your new door handle is installed and ready to use.
-

Post-Installation Check

- Verify all connections are secure
 - Test the seal of the door to ensure proper fitment. The door should be sealed tightly when both the handle is secured and the gasket is at proper thickness.
 - Check for any openings in the door seal. Closing the door on a piece of paper then attempting to pull it out would be the best method; The paper should not be able to move if that place on the gasket is completely sealed. If the paper is easy to pull out,
-

Support

If you encounter any issues during installation, consult your owner's manual or contact technical support via our contact form.