

# SRV433-5890

## Convection Blower

### INSTALLATION INSTRUCTIONS

---

#### Before Installing

- **ALWAYS** unplug the unit before beginning any work
  - Allow the unit to cool completely if recently used
  - Work in a well-lit area with proper tools
- 

#### Installation Steps

##### 1. Power Disconnection

Unplug the unit.

##### 2. Access the Unit

- Remove the front access panel toward the bottom front of the stove.
- Depending on the model, you may need to remove other parts such as the front door, knobs or fascia panels to gain access to the front access panel.

##### 3. Disconnect Blower Wiring

Disconnect the fans from the wiring harness.

##### 4. Remove Old Blower

- Remove the fastening nuts holding the blower in place
- Lift the fans out to clear the mounting bolts to remove the blower from the stove.

##### 5. Install the new Blower

- Install the new blowers in the same orientation as the original blower.

- Models such as 7100 with serial number greater than 0091588198 and Pioneer-II-BK wood stoves require 2 of these blowers for a complete replacement.
- Secure the blowers with the previously removed fastening nuts.

## 6. Connect Blower Wiring

- Connect the new blowers to the wiring harness.
- The blower wires are not polarized, so the positive/negative leads from the wiring harness can be connected to either blower wire.

## 7. Final Assembly

Reinstall the access panels and any other parts removed prior such as the front door, knobs or fascia panels that were removed.

## 8. Power Connection

Connect the stove to the power source with the power cord.

---

## Post-Installation Check

- Verify all connections are secure
- Test blower operation before closing panels
- Check for any unusual noises or vibrations

---

## Support

If you encounter any issues during installation, consult your owner's manual or contact technical support via our contact form.