

VACUUM/PRESSURE SWITCH HOSE 891121

INSTALL INSTRUCTIONS

Replaces MPNs: 891121, C-M-340-T, RP2111, EF-018, EF4i-018, H5898, 35017, & More

Before Installing

- **ALWAYS** unplug the unit before beginning any work
 - Allow the unit to cool completely if recently used
 - Work in a well-lit area with proper tools
 - Ensure there are no pellets in the hopper assembly
-

Installation Steps

1. Unplug the stove.
 2. Remove the necessary panels to gain access to the rear of the unit.
 3. Locate the vacuum/pressure switch (Pay attention to what port the hose connects to on the switch. Some units may have a switch with two ports on it. The hose must be installed on the correct port in order to function properly).
 4. Remove the old hose (One side should be connected to the pressure switch and the other will be connected to a port on the rear of the stove or combustion blower housing).
 5. Connect the new hose to the vacuum switch and stove port. The hose needs to be connected to the same parts as the previous hose.
 6. Reinstall any previously removed panels and plug in the unit.
-

Post-Installation Check

- Verify all connections are secure
- Ensure all wiring is not in proximity of moving parts

- Test motor operation before closing panels
 - Check for any unusual noises or vibrations
-

Support

If you encounter any issues during installation, consult your owner's manual or contact technical support via our [contact form](#).